

IN-LINE MULTI-PARAMETER WATER SENSOR

Chlorine, Conductivity, Pressure, Temperature

Applications: Drinking Water Security


- > Real-time, in-line monitoring of key parameters in the water distribution system
- > Detection of any changes in your water quality commonly caused by leaks, pipe corrosion and biofouling effects, etc.
- > Disinfection process optimization

Benefits

- > Real time water network monitoring
- > In-line water contaminant identification
- > Efficient control of water distribution

Main features

- > Measurement of the main disinfection species
- > No interference with chloramines
- > Chemical free operation
- > Annual maintenance and calibration
- > Easy field installation with direct insertion in pipe, under pressure, using standard collar and valve
- > Battery operated
- > Real time telemetry data transmission to a central server



General Description

The KAPTA™ 3000-AC4 probe has been specifically developed to enhance the management and control of the drinking water distribution network. The KAPTA™ 3000-AC4 monitors the important water parameters chlorine, conductivity, pressure and temperature using innovative, integrated technologies. The chlorine is measured using a three electrode amperometric sensor designed to monitor the active chlorine (HOCl). The pressure sensor uses a silicium piezoresistive cell and the conductivity is a measurement using four electrodes. These integrated sensors require no maintenance or recalibration and allow for the online monitoring of the drinking water distribution network systems.

The KAPTA™ 3000-AC4 continuously measures and stores the 24 last measurements based on the chosen data acquisition mode. The communication module (IP68) queries the probe to allow real time telemetry data transmission to a central server. All the data measured by the probe is organized into an easy to use interface for the operator.

The design of the KAPTA™ 3000-AC4 probe and its use and mode of communication have been designed to facilitate its implementation and application on site. This innovative, modern and reliable monitoring solution provides real-time control of the distributed water quality.

KAPTA™ new generation probe is the answer from ENDETEC™ to in-line water sensing needs. With a complete line of amperometric probes, KAPTA™ product range offers unique environmental detection solutions for water quality distribution networks.

YOUR WATER QUALITY UNDER CONTROL!

KAPTA 3000-AC4

IN-LINE MULTI-PARAMETER WATER SENSOR

Chlorine, Conductivity, Pressure, Temperature



Sensor Specifications

| | | | |
|-------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| General specifications | <ul style="list-style-type: none"> Detection of active chlorine (HOCl) Measurement of conductivity, pressure and temperature Reagent free multi-parameter probe Real in-situ, online active chlorine measurement Miniaturized low power consumption sensor probe | | |
| Operating range | 1. Chlorine HOCl (2X) <ul style="list-style-type: none"> HOCl: 0.01mg/l – 2.0 mg/l Measurement accuracy: ± 0.03 ppm; ± 5% Sensor output resolution: 0.01 ppm Output communication resolution: 0.01 ppm Response time : < 30s | pH range | <ul style="list-style-type: none"> 5 – 9 Lower pH than 5 can damage the sensor head irreversibly |
| | 2. Conductivity <ul style="list-style-type: none"> Range: 50 – 1000 µScm-1 Measurement accuracy: ± 5 µScm-1; ± 5% Sensor output resolution: 1 µScm-1 Output communication resolution: 5 µScm-1 3. Pressure <ul style="list-style-type: none"> Range: 0 – 10 bar (145 psi) Measurement accuracy at 25°C : ± 50mbar Measurement accuracy over temperature (0-40°C) : ± 100mbar Sensor output resolution : 2 mbar Output communication resolution: 50 mbar 4. Temperature <ul style="list-style-type: none"> Range: 0 – 40°C Measurement accuracy : ± 1.2°C Sensor output resolution: 0.2°C Communication output resolution: 0.3°C | Operating temperature range | 0 – 40 °C |
| | | Pressure | 0-10 bar, Over pressure: 30 bar (435 psi) |
| | | Long term stability | 1 year |
| | | Flowrate | Minimum 0.03 m/s Maximum 1.5 m/s (Tested over one year) |
| | | Data logging | 1. Data acquisition mode <i>Data send using RS232 under MODBUS™ protocol</i> NORMAL: 1 averaged measure every hour TURBO: 1 averaged measure every 5 min 2. Probe Data storage 24 last measurements with maximum, average and minimum measures sent in only one SMS and the last measure 3. GSM Data transmission Request to the probe: One time the 24 data NORMAL: Typically 1 time every 24 hours* TURBO: Typically 1 time every 2 hours* *(or every 15 min to 24 hours by step of 15 min) 4. Radio Data transmission Request to the probe: 6 time the last measure Transmission of 12 data (6 data read from the probe every t/6 and the 6 previous data read) TURBO : Typically 1 time every t=30 min. (or every t=30 min to t=6 hrs by step of 30 min) |
| Probe Power Supply | 3.2 – 5 V DC; Battery operated: Replaceable Battery Pack included | | |
| Probe cable length | 3 m | | |
| Probe weight | 410 g | | |
| Probe dimensions | <ul style="list-style-type: none"> The sensor has been designed to fit directly in a pipe of external diameter D > 60 mm or 2" with a threaded fitting Maximum pipe diameter: DN 300 for iron pipe and DN 250 for PVC/HDPE Length of the KAPTA™ probe : 300mm Diameter of KAPTA™ probe head 35 mm Thread 1"1/8 Gaz BSP Cylindrical | | |
| GSM Communication Module Dimensions | L= 110 x H= 240 x D=54 mm | Radio 868 MHz Communication Module Dimensions | L= 80 x H= 160 x D=70 mm |

Ordering Information

KAPTA™ 3000-AC4

IN-LINE MULTI-PARAMETER WATER SENSOR

Chlorine, Conductivity, Pressure, Temperature

ENDETEC is a trademark of Veolia Water Solutions & Technologies Group

Pathogen Detection System, Inc.

Suite 4697, Biosciences Complex, 116 Barrie Street

Kingston, Ontario, Canada K7L 3N6

Tel: (+1) 613 533 3321 - Fax: (+1) 613 533 3317

NEROXIS SA

Rue Jaquet-Droz 7, CP 216,

CH-2002 Neuchâtel 2, Switzerland

Tel: (+41) 32 720 51 51 - Fax: (+41) 32 720 57 12

www.endetec.com or email info@endetec.com



WATER

Solutions & Technologies